

[54] ALPHANUMERIC SECTION OF OFFICE
MACHINE KEYBOARDS

[76] Inventor: **W. Kenneth Ryan**, c/o William F.
Ryan, 3303 Lakeview, Cincinnati,
Ohio 45211

[21] Appl. No.: 491,752

[22] Filed: May 5, 1983

[51] Int. Cl.³ B41J 5/08

[52] U.S. Cl. 400/489; 400/82;
400/88; 400/472; 400/682; 340/365 R; D18/1

[58] Field of Search 400/82, 88, 472, 488,
400/489, 682; 84/423, 446, 447; 178/17 C;
200/5 A; 235/145 R; 248/166, 460; 269/65,
324, 325; 340/365 R, 365 S, 365 E; 434/227,
231; D17/1-9; D18/1, 7

[56] References Cited

U.S. PATENT DOCUMENTS

546.235	9/1895	Luther	296/325 ^a
3,879,602	4/1975	Walker	200/5 A
3,926,422	12/1975	Wilson	269/60
3,940,758	2/1976	Margolin	200/5 A
3,990,565	11/1976	Felton et al.	400/682
4,120,039	10/1978	Fischer	200/5 A
4,378,553	3/1983	McCall	400/82

FOREIGN PATENT DOCUMENTS

56-118120	9/1981	Japan	340/365 R
8300308	2/1983	PCT Int'l. Appl.	400/682

OTHER PUBLICATIONS

"Wallet Terminal Keyboard with Acoustic Coupler";
M. F. Davis, Jr. et al., *IBM Technical Disclosure Bulletin*;
vol. 10, No. 3, pp. 188-189; Aug. 1967.

Primary Examiner—Clifford D. Crowder
Assistant Examiner—David A. Wiecking

[57] ABSTRACT

An adjustable alphanumeric keyboard based on ISO standard format and consisting of two flat key contact mounting boards, one left and one right, corresponding respectively to the section of the alphanumeric keyboard actuated by the left hand and right hand in touch typing, joined by a hinge at a point corresponding to the keyboard C row, between columns 05 and 06, the outermost end of one mounting board connected by a hinge to the keyboard case or chassis, the outermost end of the other mounting board free to move laterally and pivot in the same plane, with means available to position said movable end, in order to give the mounting boards an adjustable angle, peaking the rows of key contacts between columns 05 and 06.

1 Claim, 7 Drawing Figures

